



Reliant Propane Burnishers

Experience the productivity of propane.

Choose from 13 hp to 20 hp propane powered engines.



Discover the superior performance and productivity built into the design of Aztec Reliant buffers. From an offset body that allows easy access under racks and in corners to the unique pad angle that eliminates side torque and dramatically increases head pressure, the economical Reliant buffer is a time and money saver. Available from stock with Kawasaki, Honda, and Onan engines.

- Rugged steel and cast aluminum body
- Unique pad angle design
- Right side offset machine body
- 13 hp Honda, 14 hp Onan, 20 hp Onan or 17 hp Kawasaki motor
- 110 volt starter or 12 volt battery with key switch
- Oil alert or low oil shut down
- Hour meter/Tachometer
- Safety regulator fuel system
- 2-3 year limited manufacturer's warranty
- UL and CGA approved, Meets CARB and EPA emissions standards

For brilliant results at amazing speed !



Propane Buffers

RELIABLE • PRODUCTIVE • ECONOMICAL

The Reliant's no nonsense design was built with the contractor in mind. Reliant is an unsurpassed value due to its Simplicity of design and productivity.

With fewer parts and longer service intervals, the machine's design minimizes field problems and expensive downtime. Dependability and ease of operation make all of Aztec's high speed floor care equipment a must for the growing Building Service Contractor or in-house professional.

21" Rated 25,000 Sq. Ft./hour

Specifications	P21H13	P21NS14
Pad Size	21"	21"
Pad Speed	2100 RPM	2100 RPM
Work Rating	25,000 sq. ft.	25,000 sq. ft.
Engine	Honda	Onan
Horsepower	13 hp	14 hp
Engine Speed	3600 RPM	3600 RPM
Fuel System	regulator system	regulator system
Oil Safety System	oil alert (buzzer)	low oil shut down
Starter	110 volt	12 volt battery w/key
Propane Tank	steel safety fill	steel safety fill
Width	23"	23"
Length	42"	42"
Height	28"	28"
Weight	185 lbs.	190 lbs.
Sound Level	88-90 db	80-82 db
Vibration	less than 2.5 mm	less than 2.5 mm
Deck	steel & cast aluminum	steel & cast aluminum
Handle	adjustable steel	adjustable steel
Motor Warranty	2 years	3 years

24" Rated 29,000 Sq. Ft./hour

Specifications	P24H13	P24K17	P24NS14
Pad Size	24"	24"	24"
Pad Speed	1850 RPM	1850 RPM	1850 RPM
Work Rating	28,000 sq. ft.	28,000 sq. ft.	28,000 sq. ft.
Engine	Honda	Kawasaki	Onan
Horsepower	13 hp	17 hp	14 hp
Engine Speed	3600 RPM	3600 RPM	3600 RPM
Fuel System	regulator system	regulator system	regulator system
Oil Safety System	oil alert (buzzer)	low oil shut down	low oil shut down
Starter	110 volt	12 volt battery w/key	12 volt battery w/key
Propane Tank	steel safety fill	steel safety fill	steel safety fill
Width	25"	25"	25"
Length	46"	46"	46"
Height	30"	30"	30"
Weight	210 lbs.	215 lbs.	215 lbs.
Sound Level	88-90 db	80-82 db	80-82 db
Vibration	less than 2.5 mm	less than 2.5 mm	less than 2.5 mm
Deck	steel & cast aluminum	steel & cast aluminum	steel & cast aluminum
Handle	adjustable steel	adjustable steel	adjustable steel
Motor Warranty	2 years	2 years	3 years

27" Rated 33,000 Sq. Ft./hour

Specifications	P27H13	P27K17	P27NS20
Pad Size	27"	27"	27"
Pad Speed	1850 RPM	1850 RPM	1850 RPM
Work Rating	33,000 sq. ft.	33,000 sq. ft.	33,000 sq. ft.
Engine	Honda	Kawasaki	Onan
Horsepower	13 hp	17 hp	20 hp
Engine Speed	3600 RPM	3600 RPM	3600 RPM
Fuel System	regulator system	regulator system	regulator system
Oil Safety System	oil alert (buzzer)	low oil shut down	low oil shut down
Starter	110 volt	12 volt battery w/key	12 volt battery w/key
Propane Tank	steel safety fill	steel safety fill	steel safety fill
Width	29"	29"	29"
Length	47"	47"	47"
Height	30"	30"	30"
Weight	223 lbs.	228 lbs.	235 lbs.
Sound Level	88-90 db	80-82 db	80-82 db
Vibration	less than 2.5 mm	less than 2.5 mm	less than 2.5 mm
Deck	steel & cast aluminum	steel & cast aluminum	steel & cast aluminum
Handle	adjustable steel	adjustable steel	adjustable steel
Motor Warranty	2 years	2 years	3 years